



Acera™ Amundsen SBA is a DNV GL type approved 12-strand high performance rope made from genuine Acera™ HMPE yarns, which is individually coated through a rotating 360° Lick-roller process.

The technology behind this innovative solution lies in the energy absorption properties of the SBA core of the rope. If the load bearing construction breaks, the SBA will absorb the snap back forces, resulting in a reduction of snap back. With safety measures like Timm Acera™ Amundsen 12 SBA, you can mitigate risks to personnel during any operations, creating a safer mooring environment. Timm Acera™ Amundsen SBA is a HMPE rope solution, using the same material composition as our best-selling premium Timm Acera™ Amundsen combined with Timm Snap Back Arrestor for improved safety when mooring, tugging, fishing.

This cumbersome single yarn coating process demonstrates the uncompromising commitment to the quality standards of Acera™. Single yarn coating is proven to significantly enhance internal and external abrasion resistance, and extend service life and strength.

12 strand ropes are regarded as the best rope construction, and has become the most common construction for HMPE ropes. Acera™ Amundsen is the alternative to the cumbersome steel wire ropes. It is stronger and safer, with significantly less snap-back/recoil. The corresponding weight is therefore 7 times lower. When replacing conventional fiber ropes, the reduction in diameter leads to significant savings in weight (60%), space and handling. This reduces the total time required for mooring operations and fuel consumption.

### SUITABLE



Fishery



Mooring



Towing

## PRODUCT FEATURES

Construction	12-strand plaited core
Fiber	Acera HMPE
Specific gravity	0,97 (floating)
Colours	Platinum, Yellow, Blue
UV resistance	Excelent
Abrasion resistance	Excelent
Acid resistance	Excelent
Alkali resistance	Excelent
Most chemicals resistance	Excelent
Water resistance	Excellent (0% absorption)
Heat resistance	Low (145-150 melting)
Elongation	Low (2-3% at break)

## KEY BENEFITS

- Reduction of snap back
- Safer operations
- Easy to splice
- Easy to inspect
- Well balanced; 6 left and 6 right strands
- Outsized surface contact - better abrasion resistance
- No rotation under load
- Single yarn coating, extended service life

## CERTIFICATE



diameter	MBL spliced	MBL spliced	MBL unspliced	MBL unspliced	diameter	MBL spliced	MBL unspliced	Weight
DIA. (mm)	(t)	(kN)	(t)	(kN)	DIA. (inch)	(lbs)	(lbs)	(kg/m)
16	23.5	230	26	255	5/8"	51.594	57.326	0.166
18	29.1	285	32.1	315	3/4"	63.733	70.815	0.201
20	34.7	340	38.7	380	13/16"	76.884	85.427	0.236
22	41.3	405	45.9	450	7/8"	91.047	101.164	0.278
24	47.9	470	53	520	1"	105.210	116.900	0.321
26	55.1	540	61.2	600	1_1/16"	121.397	134.885	0.372
28	62.7	615	69.9	685	1_1/8"	138.594	153.994	0.423
30	71.4	700	79	775	1_1/4"	156.804	174.227	0.478
32	79.5	780	88.2	865	1_5/16"	175.013	194.459	0.536
34	88.7	870	98.4	965	1_3/8"	195.246	216.940	0.597
36	98.4	965	109.1	1070	1_1/2"	216.490	240.545	0.662
38	108.1	1060	119.8	1175	1_9/16"	237.735	264.150	0.747
40	117.8	1155	131	1285	1_5/8"	259.991	288.879	0.818
44	140.2	1375	155.5	1525	1_3/4"	308.550	342.833	0.969
48	163.2	1600	181	1775	2"	359.131	399.035	1.153
52	187.6	1840	208.5	2045	2_1/8"	413.760	459.733	1.328
56	213.6	2095	237.6	2330	2_1/4"	471.423	523.804	1.515
60	241.7	2370	268.7	2635	2_1/2"	533.133	592.370	1.741
64	270.7	2655	300.8	2950	2_5/8"	596.866	663.185	1.951
68	301.3	2955	335	3285	2_3/4"	664.646	738.496	2.175
72	333.4	3270	370.7	3635	3"	735.461	817.179	2.417
76	367.1	3600	407.9	4000	3_1/8"	809.310	899.234	2.672
80	401.8	3940	446.1	4375	3_1/4"	885.183	983.537	2.972
82	419.7	4116	466.3	4573	3_3/8"	925.236	1.028.040	3.111
88	475.2	4660	528.2	5180	3_5/8"	1.048.048	1.164.498	3.546
96	554.2	5435	615.9	6040	4"	1.222.048	1.357.831	4.170
100	596	5845	662.3	6495	4_1/16"	1.314.106	1.460.118	4.538
102	617.1	6052	685.7	6724	4_1/8"	1.360.439	1.511.599	4.708
104	638.9	6265	709.7	6960	4_1/4"	1.408.188	1.564.653	4.882
108	682.7	6695	758.7	7440	4_1/2"	1.505.304	1.672.560	5.237
110	705.1	6915	783.7	7685	4_9/16"	1.554.874	1.727.638	5.420
112	728.1	7140	811	7953	4_5/8"	1.609.097	1.787.886	5.605
116	774.3	7595	860.6	8440	4_3/4"	1.707.630	1.897.367	5.986
120	822.4	8065	913.7	8960	5"	1.812.840	2.014.266	6.421